

**Product Structure Parameters**

规格 Specification	导体外径或高	计算外径 Calculated Outer Diameter mm		电缆计算重量 Calculated Weight kg/km			
芯数×截面 No.of Core× Cross Section mm <sup>2</sup>	Conductor Outer Diameter or High mm	VV-T VLV-T	VV22-T VLV22-T	VV-T	VLV-T	VV22-T	VLV22-T
3×4+1×2.5(T)	2.25	18.2	21.8	419	344	714	639
3×6+1×4(T)	2.76	19.3	22.9	515	403	827	715
3×10+1×6(T)	3.55	22.1	25.7	662	472	1018	828
3×16+1×10(T)	4.8	24.9	28.7	976	676	1389	1088
3×25+1×16(T)	6.0	28.6	32.6	1380	905	1865	1390
3×35+1×25(T)	7.0	27.5	31.5	1561	942	2028	1409
3×50+1×25(T)	8.3	30.8	35.6	2028	1154	2772	1898
3×70+1×35(T)	10.0	34.5	39.1	2762	1506	3572	2316
3×95+1×50(T)	11.6	39.9	44.9	3753	2007	4725	2753
3×120+1×70(T)	13.0	42.7	47.9	4657	2457	5586	3386
3×150+1×95(T)	14.6	47.6	53.0	5595	2886	6571	3862
3×185+1×120(T)	16.2	52.1	57.5	6996	3607	8098	4916
3×240+1×150(T)	18.4	59.0	64.6	9000	4597	10503	5733
3×300+1×150(T)	20.6	64.1	70.1	11181	5621	12874	7314
3×4+1×4(T)	2.25	18.2	21.8	440	365	735	660
3×6+1×6(T)	2.76	19.3	22.9	525	413	836	724

续表 Continued

规格 Specification	导体外径或高	计算外径 Calculated Outer Diameter mm		电缆计算重量 Calculated Weight kg/km			
芯数×截面 No.of Core×Cross Section mm <sup>2</sup>	Conductor Outer Diameter or High mm	VV-T VLV-T	VV22-T VLV22-T	VV-T	VLV-T	VV22-T	VLV22-T

3×10+1×10(T)	3.55	22.1	26.2	759	570	1122	993
3×16+1×16(T)	4.8	24.9	29.0	850	730	1267	1147
3×25+1×25(T)	6.0	28.6	33.7	1455	980	2427	1670
3×35+1×35(T)	7.0	27.5	33.1	1737	1118	2944	2070
3×50×1×50(T)	8.3	30.8	36.37	2270	1396	3830	2573
3×70+1×70(T)	10.0	34.5	42.3	3081	1824	4011	2754
3×95+1×95(T)	11.6	39.9	45.6	4178	2432	5149	3403
3×120+1×120(T)	13.0	42.7	48.8	5132	2931	6194	3993
3×150+1×150(T)	14.6	47.6	54.8	6345	3638	7567	4860
3×185+1×185(T)	16.2	52.1	59.7	7842	4452	9225	5835
3×240+1×240(T)	18.4	49.0	66.5	10088	5686	11664	7262
3×300+1×300(T)	20.6	64.1	72.1	12569	7009	14312	8752
4×4+1×2.5(T)	2.25	19.29	22.89	403	304	742	643
4×6+1×4(T)	2.76	20.47	24.07	503	354	860	711
4×10+1×6(T)	4.05	23.68	27.28	716	463	1124	871
4×16+1×10(T)	5.1	26.76	30.56	984	583	1458	1057
4×25+1×16(T)	6.42	31.31	35.91	1456	825	1871	1240
4×35+1×16(T)	6.85	31.30	35.9	1745	919	2520	1694
4×50+1×25(T)	8.13	35.06	39.66	2352	1186	3216	2050
4×70+1×35(T)	9.64	39.06	44.06	3185	1509	3316	2510
4×95+1×50(T)	11.49	45.27	50.47	4361	2013	4945	3189
4×120+1×70(T)	12.81	48.71	54.81	5356	2422	6641	3707
4×150+1×70(T)	18.29	56.15	61.55	6611	2998	8090	4477
4×185+1×95(T)	20.28	60.23	66.03	8131	3611	9778	5258